

Why Suryava?

0% negative power tolerance

- Positive power tolerance of up to 0 ~ 4.99Wp
- Module Imp binning radically reduces string mismatch losses

Improved longevity

- Excellent anti-PID performance via optimized process and materials control
- Lower susceptibility to LID & LeTID

Premium performance parameters

- HJT solar cell up to 90% bifaciality, brings higher energy yield from rear side
- Lower temperature coefficient minimizing generation losses at high temperature

Suited for rooftop installation*

- Light weight modules
- Aesthetically appealing with higher efficiency

*Modules with 120 cell



vikramsolar.com
sales@vikramsolar.com (India & ROW)
usa@vikramsolar.com (US)
europe@vikramsolar.com (Europe)

+91 90070 18200
Toll Free 1800 212 8200 (India only)
vikram-solar (India & ROW)
vikram-solar-us (USA)



LOCATIONS

India: Kolkata | Gurugram | Chennai | International: USA | Germany | China

Vikram Solar and all its accompanying logos are trademarks of Vikram Solar Limited registered in India

VRM- flyer- Suryava- Apr-2025_V04

vikramsolar
CREATING CLIMATE FOR CHANGE

BREAKING THE TECHNOLOGY CEILING



Lower susceptibility to LID & LeTID



Lower temperature coefficient



Excellent low light performance



Up to 90% bifaciality factor

SURYAVA
HIGH EFFICIENCY HJT PV MODULES



Superior hail test performance
ø 40mm hail test passed from third party laboratory

Applicable with Glass (2mm) to Glass (2mm) Module and Glass (3.2mm) to Backsheet Module



Maximum Efficiency%

23.66

Cell Type

G12 HJT

Wattage Up to

735W

Cell Number

132




Suryava, module with Heterojunction technology increases efficiency, performance, and durability to the next level.

HJT is the combination of two technologies into a single PV cell- a crystalline silicon cell sandwiched between two layers of amorphous thin-film silicon.

- The top layer of amorphous silicon catches higher spectrum of sunlight before it hits the crystalline layer
- The monocrystalline silicon, the middle layer, is responsible for turning most of the sunlight into electricity
- The final amorphous silicon layer captures the remaining photons that surpass the first two layers


This combined process allows more energy to be harvested as opposed to using them individually, resulting in efficiencies of 23% or higher.

Advantages of HJT solar cell & modules




Longer lifetime

- Modules sustain less than 0.4% YoY degradation
- Modules have top grade encapsulation and double side lamination, increasing overall resistance to harsh weather condition



Superior power generation


- Modules maintain an average of 23% efficiency on commercial label
- HJT modules having low temperature coefficient are capable to perform better at high temperatures



Best-in-class bifaciality factor

- Modules having bifaciality factor up to 90%
- Up to 30% generation gain can be achieved from rear side at suitable albedo

Why Suryava?




Prolonged safety assurance

- IP68 with potting JB provides higher level of water ingress protection
- High insulation resistance ensuring electrical safety



Excellent low-light performance

- Superior generation with wide spectral response
- Higher performance under low light scenarios



0% negative power tolerance

- Positive power tolerance of up to 0 ~ 4.99Wp
- Module Imp binning radically reduces string mismatch losses

Manufacturing of HJT module - Suryava

Highly automated production line

- Multi stage EL and digitalized visual inspection lowers defect rates
- Implemented engineering excellence ensures top notch quality
- High-capacity stringer with integrated laser cutting and string EL facility
- Double side heating and stacking laminator